



Product Data Sheet



Max Bond

006 Sports Surface Adhesive



PRODUCT DESCRIPTION

Max Bond 006 Sports Surface Adhesive is a solvent based synthetic grass and external sports surface adhesive for outdoor application. With excellent early bond strength it prevents edge curling and resists water and weather deterioration.

RECOMMENDED FOR

- Non stretch open weave polypropylene backed synthetic grass
- Needle punch polypropylene carpet
- Suitable for use over concrete, exterior grade timber, cured asphalt and paved surfaces

SURFACE PREPARATION

All phases of the installation should comply with the current Australian Standard AS1884 & AS2455. The subfloor must be clean, structurally sound, dry and free from all contaminants which will inhibit good adhesion – this includes previously used adhesive and floorcoverings, polishes, paint, waterproofing membranes, concrete curing agents and laitance (laitance being the dusty unstable toppings of poorly or insufficiently cured concrete). Deep indentations and cracks should be treated with the appropriate cementitious screed in accordance with manufacturer's instructions

COVERAGE

Approximately 1.6m² / litre when adhesive is evenly spread with a 3.2mm V-notch trowel

APPLICATION

Apply adhesive using a 'V' notched trowel spreader. Dimensions of notchings should be such as to provide a minimum (80%) coverage of adhesive to the back of the flooringcovering. As most synthetic grass and fibre bonded carpets have highly textured backings, a deep 3.2mm to a 6mm 'V' notching is strongly recommended. For hard to hold carpet, or when installing over low absorbent substrates, it is necessary to allow a longer tack up time.

Always check & ensure good transfer of adhesive to the back of the carpet.

Roll within 1 hour of laying. Do not use in rain or if rain is expected during or immediately after laying. Do not allow heavy traffic within 24 hours if installation.

Refer to AS/NZS2455.1-2007 "Textile Floor Coverings – Installation Practice" for further preparation and installation details

CLEAN UP

Trowels and other tools may be cleaned with MAX BOND SC Solvent Cleaner

SHELF LIFE

12 months in unopened containers stored out of direct sunlight, undercover and away from all sources of heat and ignition

Note: Always carry out your own test to confirm suitability of this product with your application. Additional information on physical properties, health hazards, storage, handling and transport is available in the Material Safety Data Sheet (MSDS), available on MJS web site.

STORAGE

This product is classified UN 1133 D.G. Class 3 – Hazchem 3 and is HIGHLY FLAMMABLE. This product should be stored accordingly and in line with correct regulations.

TECHNICAL DATA

Appearance:	Coloured paste (Green)
Solids:	Approx 55%
Base Polymer:	Synthetic rubber
Carrier:	Organic solvent
Flammability:	Highly flammable
Container Size:	1, 4 & 20 litre metal pail

May 2011



DISTRIBUTED BY:

QUEENSLAND

Brisbane
MJS Floorcoverings
35 Dividend St
Mansfield 4122
Ph: 07 3347 7300
Fax: 1800 063 299

NSW

Sydney
MJS Floorcoverings
7 Walker Place
Wetherill Park 2164
Ph: 02 9725 5519
Fax: 02 9725 5552

VICTORIA

Melbourne
MJS Floorcoverings
82 Endeavour St
Shine 3020
Ph: 03 9314 2872
Fax: 03 9314 6971

TASMANIA

Hobart
MJS Floorcoverings
101 Albert Rd
Moonah 7000
Ph: 03 6228 1032
Fax: 03 6228 1035

NORTHERN TERRITORY

Darwin
MJS Floorcoverings
14, 128 Coonawarra Rd
Winnellie 0821
Ph: 08 8947 6917
Fax: 08 8947 1528

SOUTH AUSTRALIA

Adelaide
Manufacturers'
Agencies Pty Ltd
Unit 7/9 William St
Mile End South 5031
Ph: 08 8234 8933
Fax: 08 8234 8955

WESTERN AUSTRALIA

Perth
Manufacturers'
Agencies Pty Ltd
28 Carbon Court
Osborne Park 6017
Ph: 08 6240 1000
Fax: 08 9445 1332