

# Product Data Sheet



## Max Bond

### 105 FAST TAC CARPET ADHESIVE



#### PRODUCT DESCRIPTION

MJS Max Bond 105 Fast Tac Carpet Adhesive is a water-based SBR Latex adhesive specifically formulated to provide a fast tack-up time with excellent "leggy" grab and holding power for jute & action backed tufted carpets, woven wilton & axminster carpets and most needle-punched carpets. Internal Use Only

#### FOR BONDING

Tufted secondary backed carpets (jute, soft and action-backed), woven wilton & axminster carpets, most needle-punched carpets as well as cushioned Double Bond underlays.

#### TO

Sound, smooth dry subfloors of concrete; conventional sand/cement screeds or underlayment; plywood; hardboard or cement sheet underlays.

#### STANDARDS

Australian/NZ Standard 2455.1.2007 – "Textile Floor Coverings Installation Practice".

#### SURFACE PREPARATION

All surfaces to be bonded shall be dry, smooth, sound and clean. Subfloors must also be free of wax, grease and hydrostatic pressure. The minimum subfloor temperature before commencing surface preparation and adhesive application is 10°C. It is recommended that all absorbent substrates be primed with Max Prime Floor & Wall primer prior to the application of adhesive.

#### TYPICAL PROPERTIES

Appearance: Light Brown  
Solids: Approx 60%  
Base Polymer: Latex  
Viscosity: Creamy Paste  
Toxicity: Non-toxic  
S.G.: Approx 1.25  
Freezability: Avoid freezing

#### APPLICATION

Apply using a 'V' notched trowel spreader, 1.6mm x 1.6mm x 1.6mm giving a spread rate up to 5m<sup>2</sup>/litre to adhere the double bond underlay to the entire subfloor area. Use a 2.4mm x 2.4mm x 2.4mm 'V' notched trowel giving a spread rate up to 3m<sup>2</sup>/litre to adhere smooth back carpet to subfloors or double bond underlay or 3.2mm x 1.6mm x 3.2mm 'V' notched trowel giving a spread rate up to 2m<sup>2</sup>/litre for coarse back, woven or action back carpets to subfloors or double bond underlay.

Check to ensure that complete transfer of adhesive to the carpet/underlay has occurred. Roll finished installation with a 25-35Kg roller. Complete the installation according to the adhesive & floorcovering manufacturer's instruction. Do not allow heavy traffic for 24 hours. All Seams should be seamed sealed using a suitable seam sealer. It is strongly recommended that Max Seam Double bond tape be used on all seams in double bond installations.

#### CLEAN UP

Clean tools immediately after use with warm soapy water. Dried adhesive may be cleaned off using a solvent cleaner applied to a damp cloth then rubbed gently over the dried adhesive.

#### SHELF LIFE

Up to 12 months from manufacturing date in sealed container at 20°C.

Note: Always carry out your own test to confirm suitability of this product with your application. Additional information on physical properties, health hazards, storage, handling and transport is available in the Material Safety Data Sheet (MSDS), available on MJS web site.

#### STORAGE

Recommended to be at temperatures between 10 and 30 degrees Celsius. Keep in well-ventilated area away from sources of heat.

#### CONTAINER SIZES

15 litre plastic pails



May 2011

#### DISTRIBUTED BY:

##### QUEENSLAND

**Brisbane**  
MJS Floorcoverings  
35 Dividend St  
Mansfield 4122  
Ph: 07 3347 7300  
Fax: 1800 063 299

##### NSW

**Sydney**  
MJS Floorcoverings  
7 Walker Place  
Wetherill Park 2164  
Ph: 02 9725 5519  
Fax: 02 9725 5552

##### VICTORIA

**Melbourne**  
MJS Floorcoverings  
82 Endeavour St  
Shrine 3020  
Ph: 03 9314 2872  
Fax: 03 9314 6971

##### TASMANIA

**Hobart**  
MJS Floorcoverings  
101 Albert Rd  
Moonah 7000  
Ph: 03 6228 1032  
Fax: 03 6228 1035

##### NORTHERN TERRITORY

**Darwin**  
MJS Floorcoverings  
14, 128 Coonawarra Rd  
Winnellie 0821  
Ph: 08 8947 6917  
Fax: 08 8947 1528

##### SOUTH AUSTRALIA

**Adelaide**  
Manufacturers'  
Agencies Pty Ltd  
Unit 7/9 William St  
Mile End South 5031  
Ph: 08 8234 8933  
Fax: 08 8234 8955

##### WESTERN AUSTRALIA

**Perth**  
Manufacturers'  
Agencies Pty Ltd  
28 Carbon Court  
Osborne Park 6017  
Ph: 08 6240 1000  
Fax: 08 9445 1332