



Armstrong installation and maintenance products have been specially developed for vinyl floors.

The complete Armstrong system includes:

- Adhesives
- Tools & Equipment
- Floor Care Products
- Complete Range of Vinyl Extrusions

PRODUCT DESCRIPTION

Armstrong SC-100 is a solvent based contact adhesive.

USAGE

For installation of:

- Vinyl extrusions
- Vinyl floor coverings
- Vinyl wall coverings

BONDS TO

Most common building substrates, such as:

- Concrete
- Cement render
- Plaster board and fibre cement wall sheet

SPECIAL PROPERTIES

- Easy application
- Fast drying
- Rapid grab

SC-100

Contact Adhesive

Easy application

Fast drying

Rapid grab





SC-100 Solvent Contact

DIRECTIONS

- Substrate preparation and installation must conform to Australian Standards
- Substrate must be structurally sound, dimensionally stable, clean, dry and dust free
- Contaminants such as paints, crayons, grease, curing agents and bond breakers should be removed mechanically by grinding or shot blasting
- Acclimatise material to job conditions at between 15°C and 30°C for 24 hours prior to installation, maintain these temperatures during and after installation
- Stir well before using. Any liquid on the surface should be stirred into the adhesive
- Keep container tightly covered when not using
- Ensure backing of Armstrong extrusion, floor or wall sheet is clean and free of dust
- Brush or roll (medium nap roller) Armstrong SC-100 Contact adhesive on to the material backing (ensuring full coverage)
- Brush or roll (medium nap roller) Armstrong SC-100 Contact Adhesive on to the substrate (ensuring full coverage)
- Allow both surfaces to dry for 10-15 minutes until "touch dry"
- Ensure material is positioned correctly and fits neatly to substrate
- Position coated surfaces accurately and bond together by applying pressure with a hand roller over the entire area
- Remove adhesive from floor and tools with mineral turpentine, care should be taken to ensure no damage occurs to the surrounding surfaces (test in an inconspicuous area)

WARNING Highly Flammable irritant. Do not use near naked flame, fire, sparks or pilot light.

COVERAGE

Approx 3–4 m²/ltr

STORAGE/HANDLING

- Keep from freezing
- Shelf life is one year from date of manufacture if unopened
- Dispose of responsibly

NOTE: Do not reuse container. Dispose of container and adhesive residue in accordance with Federal, State and Local bodies waste disposal regulations. Do not flush adhesive down drains.

SAFETY PRECAUTIONS

Avoid eye and skin contact. If eye contact occurs, flush with water for 15 minutes and call physician. Do not take internally. If swallowed, do not induce vomiting, call physician immediately. After use wash skin thoroughly with soap and water.

During the installation process, adequate ventilation of the work area should be maintained, without causing the entry of contaminants to other parts of building. Persons who are sensitive to odours and/or chemicals should avoid the work area.

EXISTING RESILIENT FLOORING

WARNING Do not sand, dry sweep, dry scrape, drill, saw, bead blast, or mechanically chip or pulverise existing resilient flooring, backing, lining felt or asphaltic 'cut-back' adhesives. These products may contain either asbestos fibres or crystalline silica.

Avoid creating dust. Inhalation of such dust is a cancer and respiratory tract hazard.

Smoking by individuals exposed to asbestos fibres greatly increases the risk of serious bodily harm.

Unless positively certain that the product to be removed is a non-asbestos containing material, you must presume it contains asbestos. Regulations may require that the material be tested to determine asbestos content.

The warnings and guidance contained in these instructions in relation to the potential for asbestos in floor covering materials are given in good faith. However, regulations, codes and directives as to the best method of handling asbestos are under continual revision. It is the obligation of the installer to ensure that practises used are safe, without risk to health, and meet all legal requirements.

WARRANTY

IMPORTANT NOTICE TO PURCHASER – As the use of this product is beyond the manufacturer's control, liability is restricted to a replacement of any material proved faulty and the manufacturer is not responsible for any loss or damage arising from failure to follow the instructions for use.

CAUTION

**KEEP OUT OF REACH OF CHILDREN
IF SWALLOWED SEEK MEDICAL ADVICE**

MATERIAL SAFETY DATA SHEET

For a copy of a Material Safety Data Sheet or for Technical information please contact Armstrong Customer Service.

Free Call 1800 632 624 (Australia Only)

Email customer_services@armstrong.com

MADE IN AUSTRALIA FOR ARMSTRONG WORLD

INDUSTRIES (AUSTRALIA) PTY LTD
29-39 MILLS ROAD, BRAESIDE VIC 3195
Ph. 03 9586 5500 Fax. 03 9580 4810
www.armstrong-aust.com.au