



Max Bond



106 Contract Carpet Adhesive

PRODUCT DESCRIPTION

MJS Max Bond 106 Contract Carpet Adhesive is a water-based SBR Latex adhesive specifically formulated to provide extra open time for positioning of long runs of commercial carpet before it develops its "leggy" grab and holding power for jute & action backed tufted carpets, woven wilton & axminster carpets and most needle-punched carpets. Internal use only

FOR BONDING

Tufted secondary backed carpets (jute, soft and action-backed), woven wilton & axminster carpets, most needle-punched carpets as well as cushioned Double Bond underlays.

TO

Sound, smooth dry subfloors of concrete; conventional sand/cement screeds or underlayment; plywood; hardboard or cement sheet underlays.

STANDARDS

Australian/NZ Standard 2455.1.2007 – "Textile Floor Coverings Installation Practice".

SURFACE PREPARATION

All surfaces to be bonded shall be dry, smooth, sound and clean. Subfloors must also be free of wax, grease and hydrostatic pressure. The minimum subfloor temperature before commencing surface preparation and adhesive application is 10°C. It is recommended that all absorbent substrates be primed with Max Prime Floor & Wall primer prior to the application of adhesive. Substrate must be absorbent to enable the adhesive to dry & cure.

TECHNICAL DATA

Appearance: Cream / White
Solids: Approx 60%
Base Polymer: Latex
Viscosity: Creamy Paste
Toxicity: Non-toxic
S.G.: Approx 1.25
Freezability: Avoid freezing

APPLICATION

Apply using a 'V' notched trowel spreader, 1.6mm x 1.6mm x 1.6mm giving a spread rate up to 5m²/litre to adhere the double bond underlay to the entire subfloor area. Use a 2.4mm x 2.4mm x 2.4mm 'V' notched trowel giving a spread rate up to 3m²/litre to adhere smooth back carpet to subfloors or double bond underlay or 3.2mm x 1.6mm x 3.2mm 'V' notched trowel giving a spread rate up to 2m²/litre for coarse back, woven or action back carpets to subfloors or double bond underlay.

Check to ensure that complete transfer of adhesive to the carpet/underlay has occurred. Roll finished installation with a 25-35Kg roller. Complete the installation according to the adhesive & floorcovering manufacturer's instruction. Do not allow heavy traffic for 24 hours. All Seams should be seamed sealed using a suitable seam sealer. It is strongly recommended that Max Seam Double bond tape be used on all seams in double bond installations.

CLEAN UP

Clean tools immediately after use with warm soapy water. Dried adhesive may be cleaned off using a solvent cleaner applied to a damp cloth then rubbed gently over the dried adhesive.

SHELF LIFE

Up to 12 months from manufacturing date in sealed container at 20°C.

Note: Always carry out your own test to confirm suitability of this product with your application. Additional information on physical properties, health hazards, storage, handling and transport is available in the Material Safety Data Sheet (MSDS), available on MJS web site.

STORAGE

Recommended to be at temperatures between 10 and 30 degrees Celsius. Keep in well-ventilated area away from sources of heat.

CONTAINER SIZES

15 litre plastic pails

May 2011



DISTRIBUTED BY:

QUEENSLAND

Brisbane
MJS Floorcoverings
35 Dividend St
Mansfield 4122
Ph: 07 3347 7300
Fax: 1800 063 299

NSW

Sydney
MJS Floorcoverings
7 Walker Place
Wetherill Park 2164
Ph: 02 9725 5519
Fax: 02 9725 5552

VICTORIA

Melbourne
MJS Floorcoverings
82 Endeavour St
Sunshine 3020
Ph: 03 9314 2872
Fax: 03 9314 6971

TASMANIA

Hobart
MJS Floorcoverings
101 Albert Rd
Moonah 7000
Ph: 03 6228 1032
Fax: 03 6228 1035

NORTHERN TERRITORY

Darwin
MJS Floorcoverings
14, 128 Coonawarra Rd
Winnellie 0821
Ph: 08 8947 6917
Fax: 08 8947 1528

SOUTH AUSTRALIA

Adelaide
Manufacturers'
Agencies Pty Ltd
Unit 7/9 William St
Mile End South 5031
Ph: 08 8234 8933
Fax: 08 8234 8955

WESTERN AUSTRALIA

Perth
Manufacturers'
Agencies Pty Ltd
28 Carbon Court
Osborne Park 6017
Ph: 08 6240 1000
Fax: 08 9445 1332