

Product Data Sheet



MAX BOND ENVIRO

2009 "Super" P.S Adhesive



PRODUCT DESCRIPTION

MAX BOND ENVIRO 2009 Pressure Sensitive adhesive is Low VOC that conforms to the Green Star Building Standards and has been developed for the installation of vinyl composition tiles. It is also suitable for the installation of Carpet Tiles and slab underlay's used in the double bond carpet installation. It has good plasticiser resistance. Internal use only

SURFACE PREPARATION

To be in accordance with The current Australian/NZ Standard 1884 & 2455 All surfaces to be bonded shall be dry, smooth, sound and clean. Subfloors must also be free of wax, grease and hydrostatic pressure. The minimum subfloor temperature before commencing surface preparation and adhesive applications 10 degrees C.

Highly absorbent wooden or concrete subfloor surfaces are to be primed with MAX BOND Primer prior to the application of adhesive.

All concrete substrate floors should be tested for moisture content, according to the above Australian/NZ Standard prior to undertaking surface priming or installation of floorcoverings.

DIRECTION FOR USE

For the installation of composition tiles, textured backed double bond underlays & Carpet Tiles to double bond underlay apply adhesive using a 1.6mm x 1.6mm x 1.6mm "V" notched spreader with approx coverage of 5m² per litre for.

When installing Carpet Tiles and smooth backed Double Bond underlay, use a long nap roller with approx coverage of 7m² per litre.

MAX BOND ENVIRO 2009 has been designed to be used in dry mode ie allow the adhesive film to completely dry and become clear.

Clear is when the adhesive changes from white wet adhesive to dry clear tacky film of adhesive. Clear time will depend on atmospheric conditions.

Complete installation according to manufacture instructions. Roll installation on completion with the recommended weight roller.

Do not allow heavy traffic for 24 hours

CLEAN UP

Clean tools immediately after use with warm soapy water.

Dried adhesive may be softened using a suitable solvent.

TYPICAL PROPERTIES

Base: Acrylic
Solids: Approx 50%
Shelf Life: 12 months from manufacturing date in sealed container at 20°C
Packaging: 4 & 15 Litre pails

Note: Always carry out your own test to confirm suitability of this product with your application. Additional information on physical properties, health hazards, storage, handling and transport is available in the Material Safety Data Sheet (MSDS), available on MJS web site.

May 2011



DISTRIBUTED BY:

QUEENSLAND
Brisbane
MJS Floorcoverings
35 Dividend St
Mansfield 4122
Ph: 07 3347 7300
Fax: 1800 063 299

NSW
Sydney
MJS Floorcoverings
7 Walker Place
Wetherill Park 2164
Ph: 02 9725 5519
Fax: 02 9725 5552

VICTORIA
Melbourne
MJS Floorcoverings
82 Endeavour St
Sunshine 3020
Ph: 03 9314 2872
Fax: 03 9314 6971

TASMANIA
Hobart
MJS Floorcoverings
101 Albert Rd
Moonah 7000
Ph: 03 6228 1032
Fax: 03 6228 1035

NORTHERN TERRITORY
Darwin
MJS Floorcoverings
14, 128 Coonawarra Rd
Winnellie 0821
Ph: 08 8947 6917
Fax: 08 8947 1528

SOUTH AUSTRALIA
Adelaide
Manufacturers'
Agencies Pty Ltd
Unit 7/9 William St
Mile End South 5031
Ph: 08 8234 8933
Fax: 08 8234 8955

WESTERN AUSTRALIA
Perth
Manufacturers'
Agencies Pty Ltd
28 Carbon Court
Osborne Park 6017
Ph: 08 6240 1000
Fax: 08 9445 1332