



MAX BOND ENVIRO

2010 Cush 'n' Lay Double-Bond Carpet Adhesive



PRODUCT DESCRIPTION

MAX BOND ENVIRO 2010 Cush 'n' Lay Double-Bond Carpet adhesive is a synthetic latex base adhesive. The adhesive has special features such as fast tack build and prolonged rebond time with low VOC that conforms to the Green Star Building Standards. Internal use only

FOR BONDING

Cush 'n' Lay Double-Bond carpet Cushion to subfloors and both tufted secondary backed carpets (jute, soft and action-backed), woven wilton & axminster carpets, most needle-punched carpets as well as cushioned Double Bond underlays. Can also be used for the direct-stick installation of these carpets.

TO

Sound, smooth dry subfloors of concrete; conventional sand/cement screeds or underlayment; plywood; hardboard or cement sheet underlays. Warning: If the carpet has non-porous backing it is essential that the subfloor be absorbent to enable the adhesive to dry and cure.

STANDARDS

Australian/NZ Standard 2455.1.2007 – "Textile Floor Coverings Installation Practice".

SURFACE PREPARATION

All surfaces to be bonded shall be dry, smooth, sound and clean. Subfloors must also be free of wax, grease and hydrostatic pressure. The minimum subfloor temperature before commencing surface preparation and adhesive application is 10°C. It is recommended that all absorbent substrates be primed with Max Bond Primer prior to the application of adhesive. Substrate must be absorbent to enable the adhesive to dry & cure.

TECHNICAL DATA

Appearance: Cream / White
Solids: Approx 68%
Base Polymer: Latex
Viscosity: Creamy Paste
Toxicity: Non-toxic
S.G.: Approx 1.25
Freezability: Avoid freezing

APPLICATION

Apply using a 'V' notched trowel spreader, 1.6mm x 1.6mm x 1.6mm giving a spread rate up to 5m²/litre to adhere the double bond underlay to the entire subfloor area. Use a 2.4mm x 2.4mm x 2.4mm 'V' notched trowel giving a spread rate up to 3m²/litre to adhere smooth back carpet to subfloors or double bond underlay or 3.2mm x 1.6mm x 3.2mm 'V' notched trowel giving a spread rate up to 2m²/litre for coarse back, woven or action back carpets to subfloors or double bond underlay.

Check to ensure that complete transfer of adhesive to the carpet/underlay has occurred. Roll finished installation with a 25-35Kg roller. Complete the installation according to the adhesive & floorcovering manufacturer's instruction. Do not allow heavy traffic for 24 hours. All Seams should be seamed sealed using a suitable seam sealer. It is strongly recommended that Dual bond seaming tape be used on all seams in double bond installations.

CLEAN UP

Clean tools immediately after use with warm soapy water. Dried adhesive may be cleaned off using a solvent cleaner applied to a damp cloth then rubbed gently over the dried adhesive.

SHELF LIFE

Up to 12 months from manufacturing date in sealed container at 20°C.

Note: Always carry out your own test to confirm suitability of this product with your application. Additional information on physical properties, health hazards, storage, handling and transport is available in the Material Safety Data Sheet (MSDS), available on MJS web site.

STORAGE

Recommended to be at temperatures between 10 and 30 degrees Celsius. Keep in well-ventilated area away from sources of heat.

CONTAINER SIZES

15 litre plastic pails

May 2011



DISTRIBUTED BY:

QUEENSLAND
Brisbane
MJS Floorcoverings
35 Dividend St
Mansfield 4122
Ph: 07 3347 7300
Fax: 1800 063 299

NSW
Sydney
MJS Floorcoverings
7 Walker Place
Wetherill Park 2164
Ph: 02 9725 5519
Fax: 02 9725 5552

VICTORIA
Melbourne
MJS Floorcoverings
82 Endeavour St
Sunshine 3020
Ph: 03 9314 2872
Fax: 03 9314 6971

TASMANIA
Hobart
MJS Floorcoverings
101 Albert Rd
Moonah 7000
Ph: 03 6228 1032
Fax: 03 6228 1035

NORTHERN TERRITORY
Darwin
MJS Floorcoverings
14, 128 Coonawarra Rd
Winnellie 0821
Ph: 08 8947 6917
Fax: 08 8947 1528

SOUTH AUSTRALIA
Adelaide
Manufacturers'
Agencies Pty Ltd
Unit 7/9 William St
Mile End South 5031
Ph: 08 8234 8933
Fax: 08 8234 8955

WESTERN AUSTRALIA
Perth
Manufacturers'
Agencies Pty Ltd
28 Carbon Court
Osborne Park 6017
Ph: 08 6240 1000
Fax: 08 9445 1332