

# Product Data Sheet



## MAX BOND ENVIRO

### TTA TexTile Adhesive

#### PRODUCT DESCRIPTION

MAX BOND ENVIRO TTA TexTile Adhesive is Low VOC that conforms to the Green Star Building Standard. It is a high performance adhesive designed for the installation of Textile / Felt backed Vinyl only over absorbent substrates. **It is not suitable or recommended for the installation of PVC Backed floorcovering Products.**

#### SURFACE PREPARATION

To be in accordance with The current Australian/NZ Standard 1884 "Floor Coverings – Resilient Sheet and Tiles – Laying and Maintenance Practices". All surfaces to be bonded shall be dry, smooth, sound and clean. Subfloors must also be free of wax, grease and hydrostatic pressure. The minimum subfloor temperature before commencing surface preparation and adhesive applications is 10 degrees C. Substrate must be absorbent to enable the adhesive to dry & cure.

Absorbent wooden or concrete subfloor surfaces are to be primed with MAX BOND Primer prior to the application of adhesive.

All concrete substrate floors should be tested for moisture content, according to the above Australian/NZ Standard prior to undertaking surface priming or installation of floorcoverings.

#### APPLICATION

Spread adhesive with a 1.6mm x 1.6mm x 1.6mm 'V' Notched trowel. Install floorcoverings into wet adhesive and ensuring complete wet transfer of adhesive to back of floorcovering.

Complete installation according to vinyl manufacturer's instructions, ensuring the installation is rolled in both directions with the recommended roll weight, prior to the adhesive curing. Do not allow heavy traffic for 24 hours.

All seams for domestic vinyl should be seam-sealed using suitable vinyl seam sealer.

#### CLEAN UP

Clean tools immediately after use with warm soapy water. Dried adhesive on tools may be cleaned off using a solvent cleaner applied to a damp cloth then rubbed gently over the dried adhesive.

#### TYPICAL PROPERTIES

Appearance	Cream / White
Base	Latex
Solids	Approx 62%
Viscosity	Creamy Paste
Shelf Life	Up to 1 year in sealed container at 20°C
Freezability	Do not freeze
Container Size	15 Litre plastic pail
<b>COVERAGE</b>	Up to 5m <sup>2</sup> per litre using "V1" Trowel

**March 2014** Note: Always carry out your own test to confirm suitability of this product with your application. Additional information on physical properties, health hazards, storage, handling and transport is available in the Material Safety Data Sheet (MSDS), available on MJS web site.

#### DISTRIBUTED BY:

##### QUEENSLAND

**Brisbane**  
MJS Floorcoverings  
35 Dividend St  
Mansfield 4122  
Ph: 07 3347 7300  
Fax: 1800 063 299

##### NSW

**Sydney**  
MJS Floorcoverings  
7 Walker Place  
Wetherill Park 2164  
Ph: 02 9725 5519  
Fax: 02 9725 5552

##### VICTORIA

**Melbourne**  
MJS Floorcoverings  
82 Endeavour St  
Sunshine 3020  
Ph: 03 9314 2872  
Fax: 03 9314 6971

##### TASMANIA

**Hobart**  
MJS Floorcoverings  
101 Albert Rd  
Moonah 7000  
Ph: 03 6228 1032  
Fax: 03 6228 1035

##### NORTHERN TERRITORY

**Darwin**  
MJS Floorcoverings  
14, 128 Coonawarra Rd  
Winnellie 0821  
Ph: 08 8947 6917  
Fax: 08 8947 1528

##### SOUTH AUSTRALIA

**Adelaide**  
Manufacturers'  
Agencies Pty Ltd  
Unit 7/9 William St  
Mile End South 5031  
Ph: 08 8234 8933  
Fax: 08 8234 8955

##### WESTERN

**AUSTRALIA**  
**Perth**  
Manufacturers'  
Agencies Pty Ltd  
28 Carbon Court  
Osborne Park 6017  
Ph: 08 6240 1000  
Fax: 08 9445 1332