



## Max Bond

### 101 Skirting Contact Adhesive



#### PRODUCT DESCRIPTION

Max Bond 101 Skirting Contact Adhesive is a specifically formulated high solids, high heat resistant, non-stringing solvent based adhesive. It is a fast drying, brushable or rollable, contact adhesive, displaying high early bond strength. Max Bond 101 Skirting Contact Adhesive is designed for use on most types of vinyl skirting and PVC mouldings. Suitable for all types of subfloors including concrete, wood, metal, ceramic, terrazzo and concrete. Ideal for bonding most types of conventional interior carpet to stair treads and risers. *Not recommended for exterior application.*

#### SURFACE PREPARATION

Ensure the surface is even, clean, dry and free from oil, dust or other contaminants.

#### APPLICATION

Mix thoroughly before use. Adhesive must be brushed or rolled onto both surfaces using appropriate brush or roller. Allow solvent to evaporate and adhesive to become touch dry. This will take approx. 10-15 minutes depending on substrate porosity, texture, ambient temperature and airflow. Ideally the surfaces should be brought together within 45 minutes. On porous surfaces a second application of adhesive may be required. Pressure should be applied to the entire area once surfaces are brought together. Do not apply adhesive if temperature is below 10°C.

Refer to AS/NZS2455.1-2007 "Textile Floor Coverings – Installation Practice" and current AS1884 for further preparation and installation details.

#### CLEAN UP

While adhesive is still wet or tacky, clean up with MAX BOND SC Solvent Cleaner. **Note:** MAX BOND SC is not recommended for removing adhesive from vinyl & carpet or finished surfaces.

#### STORAGE

Store in moderately cool and dry conditions, preferably suspended off the concrete substrate. In cold climates, product should be stored at approx. 21 °C on pallets or racks, providing clearance from concrete floors.

#### TYPICAL PROPERTIES

Appearance:	Liquid Base: Polychloroprene rubber
Viscosity:	Thin Syrup
Tack Up:	Approx 10 – 15 minutes at 20°C
Open Time:	Approx 45 minutes
Shelf Life:	12 months from date of manufacture when stored in a cool, dry, environment
Flammable Liquid:	3

**PACKAGING:** 4 litre cans and 20 litre metal pails  
Coverage Approx 3 - 4m<sup>2</sup> per litre

Note: Always carry out your own test to confirm suitability of this product with your application. Additional information on physical properties, health hazards, storage, handling and transport is available in the Material Safety Data Sheet (MSDS), available on MJS web site.

May 2011



#### DISTRIBUTED BY:

##### QUEENSLAND Brisbane

MJS Floorcoverings  
35 Dividend St  
Mansfield 4122  
Ph: 07 3347 7300  
Fax: 1800 063 299

##### NSW Sydney

MJS Floorcoverings  
7 Walker Place  
Wetherill Park 2164  
Ph: 02 9725 5519  
Fax: 02 9725 5552

##### VICTORIA Melbourne

MJS Floorcoverings  
82 Endeavour St  
Sunshine 3020  
Ph: 03 9314 2872  
Fax: 03 9314 6971

##### TASMANIA Hobart

MJS Floorcoverings  
101 Albert Rd  
Moonah 7000  
Ph: 03 6228 1032  
Fax: 03 6228 1035

##### NORTHERN TERRITORY Darwin

MJS Floorcoverings  
14, 128 Coonawarra Rd  
Winnellie 0821  
Ph: 08 8947 6917  
Fax: 08 8947 1528

##### SOUTH AUSTRALIA Adelaide

Manufacturers'  
Agencies Pty Ltd  
Unit 7/9 William St  
Mile End South 5031  
Ph: 08 8234 8933  
Fax: 08 8234 8955

##### WESTERN AUSTRALIA Perth

Manufacturers'  
Agencies Pty Ltd  
28 Carbon Court  
Osborne Park 6017  
Ph: 08 6240 1000  
Fax: 08 9445 1332