

# Product Data Sheet



## Max Bond

### 107 HI-GRAB SHEET VINYL ADHESIVE



#### PRODUCT DESCRIPTION

MJS Max Bond 107 Hi-Grab Sheet Vinyl Adhesive is a high performance acrylic based adhesive designed for the installation of commercial and domestic sheet vinyl.

It has an excellent plasticizer resistance and is formulated to provide quick initial grab and exhibit excellent "re-bond" characteristics. Internal use only

#### SURFACE PREPARATION

To be in accordance with The current Australian Standard 1884 "Floor Coverings – Resilient Sheet and Tiles – Laying and Maintenance Practices". All surfaces to be bonded shall be dry, smooth, sound and clean. Subfloors must also be free of wax, grease and hydrostatic pressure. The minimum subfloor temperature before commencing surface preparation and adhesive applications is 10 degrees C. Substrate must be absorbent to enable the adhesive to dry & cure.

Absorbent wooden or concrete subfloor surfaces are to be primed with MJS Max Prime prior to the application of adhesive.

All concrete substrate floors should be tested for moisture content, according to the above Australian Standard prior to undertaking surface priming or installation of floorcoverings.

#### APPLICATION

Spread adhesive with a 1.6mm x 1.6mm x 1.6mm 'V' Notched trowel. Some domestic sheet vinyl may require a fine 1.6 x 0.8 x 0.8mm trowel to prevent adhesive "show trough" Adhesive may be allowed to tack-up before floorcoverings is lowered. Tack-up time will depend upon atmospheric conditions.

If no tack or holding power has developed, wait five minutes before rechecking every few minutes thereafter.

Always ensure you have good wet adhesive transfer to back of floorcovering.

Complete installation according to vinyl manufacturer's instructions, ensuring the installation is rolled in both directions with the

recommended roll weight, prior to the adhesive curing. Do not allow heavy traffic for 24 hours.

All seams for domestic vinyl should be seam-sealed using Max Bond VSS vinyl seam sealer.

#### CLEAN UP

Clean tools immediately after use with warm soapy water. Dried adhesive on tools may be cleaned off using a solvent cleaner applied to a damp cloth then rubbed gently over the dried adhesive.

#### TYPICAL PROPERTIES

Appearance	Cream / White
Base	Acrylic
Solids	Approx 72%
Viscosity	Creamy Paste
Shelf Life	Up to 1 year from manufacturing date in sealed container at 20°C
Freezability	Do not freeze
Container Size	1, 4 & 15 Litre plastic pail
Trowel Size	1.6mm x 1.6mm x 1.6mm 'V' notched

**COVERAGE** Up to 5m<sup>2</sup> per litre using "V1" Trowel

Note: Always carry out your own test to confirm suitability of this product with your application. Additional information on physical properties, health hazards, storage, handling and transport is available in the Material Safety Data Sheet (MSDS), available on MJS web site.

**March 2012**



#### DISTRIBUTED BY:

**QUEENSLAND**  
**Brisbane**  
MJS Floorcoverings  
35 Dividend St  
Mansfield 4122  
Ph: 07 3347 7300  
Fax: 07 3343 9792

**NSW**  
**Sydney**  
MJS Floorcoverings  
7 Walker Place  
Wetherill Park 2164  
Ph: 02 9725 5519  
Fax: 02 9725 5552

**VICTORIA**  
**Melbourne**  
MJS Floorcoverings  
82 Endeavour Way  
Sunshine 3020  
Ph: 03 9314 2872  
Fax: 03 9314 6971

**TASMANIA**  
**Hobart**  
MJS Floorcoverings  
101 Albert Rd  
Moonah 7000  
Ph: 03 6228 1032  
Fax: 03 6228 1035

**NORTHERN TERRITORY**  
**Darwin**  
MJS Floorcoverings  
14/128 Coonawarra Rd  
Winnellie 0821  
Ph: 08 8947 6917  
Fax: 08 8947 1528

**SOUTH AUSTRALIA**  
**Adelaide**  
Manufacturers'  
Agencies Pty Ltd  
Unit 7/9 William St  
Mile End South 5031  
Ph: 08 8234 8933  
Fax: 08 8234 8955

**WESTERN AUSTRALIA**  
**Perth**  
Manufacturers'  
Agencies Pty Ltd  
28 Carbon Court  
Osborne Park 6017  
Ph: 08 6240 1000  
Fax: 08 9445 1332