

Product Data Sheet



MAX BOND ENVIRO

2001 True Set Timber Adhesive

PRODUCT DESCRIPTION

Maxbond Enviro 2001 Tru Set Timber adhesive is a one-part moisture cure Polyurethane Adhesive. It is solvent free and low in VOC content. When fully cured it forms a water resistant flexible film. 2001 Tru Set is 100% solids and has excellent sound absorbing qualities.

For Bonding: Specially formulated for the installation of both block, mosaic parquetry, engineered wood floors, laminated timber & Sheet timber flooring.

TO

Sound, smooth dry subfloors of concrete, plywood or cement sheet underlays and most common building substrates. 2001 Tru Set Polyurethane Adhesive can be adhered directly to most common epoxy "Moisture Barriers".

SURFACE PREPARTION

All surfaces to be bonded should be dry, smooth, and free of any contaminates that may affect final bond. All surfaces must be prepared in accordance with current Australian/NZ Standards 1884 Floor Coverings Resilient Sheet including moisture testing. The minimum sub floor temperature prior to commencing preparation or adhesive application is 10°C.

It is strongly recommended that Enviro 2000 Tru Seal Moisture Barrier be used over concrete floors prior to installing Timber Floorcoverings.

DIRECTION FOR USE

Apply adhesive using a 3 - 4mm "V" notched spreader. Coverage should be in the vicinity of 1.5m² per litre. Floorcovering should be laid into wet adhesive. Complete installation according to manufactures instructions. Do not allow heavy traffic for 24 hours.

CLEAN UP

Clean tools immediately using Max Bond Solvent Cleaner. Mechanical means are necessary when dry.

TYPICAL PROPERTIES

Appearance	Beige / Brown
Base	Polyurethane
Solids	Approx 100%
Viscosity	Trowellable
Shelf Life	Up to 1 year from manufacturing date in sealed container at 20°C
Freezability	Do not freeze
Packaging	10 Litre Metal pail & 600ml Sausages

Note: Always carry out your own test to confirm suitability of this product with your application. Additional information on physical properties, health hazards, storage, handling and transport is available in the Material Safety Data Sheet (MSDS), available on MJS web site

May 2011



DISTRIBUTED BY:

QUEENSLAND

Brisbane
MJS Floorcoverings
35 Dividend St
Mansfield 4122
Ph: 07 3347 7300
Fax: 1800 063 299

NSW

Sydney
MJS Floorcoverings
7 Walker Place
Wetherill Park 2164
Ph: 02 9725 5519
Fax: 02 9725 5552

VICTORIA

Melbourne
MJS Floorcoverings
82 Endeavour St
Sunshine 3020
Ph: 03 9314 2872
Fax: 03 9314 6971

TASMANIA

Hobart
MJS Floorcoverings
101 Albert Rd
Moonah 7000
Ph: 03 6228 1032
Fax: 03 6228 1035

NORTHERN TERRITORY

Darwin
MJS Floorcoverings
14, 128 Coonawarra Rd
Winnellie 0821
Ph: 08 8947 6917
Fax: 08 8947 1528

SOUTH AUSTRALIA

Adelaide
Manufacturers'
Agencies Pty Ltd
Unit 7/9 William St
Mile End South 5031
Ph: 08 8234 8933
Fax: 08 8234 8955

WESTERN

AUSTRALIA
Perth
Manufacturers'
Agencies Pty Ltd
28 Carbon Court
Osborne Park 6017
Ph: 08 6240 1000
Fax: 08 9445 1332