



Technical Data Sheet

Timber Set

Latex Timber to Timber Flooring Adhesive

Description

Timber Set is a high solids, water based latex adhesive that dries to form a strong bond between timber.

Timber Set is specially formulated for adhering mosaic, or timber veneer to timber substrates.

Features & Benefits

- High Solids content
- Water based, easy to clean
- Non flammable
- Economical
- Easy to apply

Recommended Uses

- Mosaic
- Veneer

Application Instructions

Ensure all timber substrates are clean, dry, smooth, free from dirt, wax, oil and any coatings or adhesives.

Application

Apply adhesive onto the surface using a 3mm x 3mm V notched spreader. Spread only about 1 square metre at a time to ensure 100% adhesive transfer to the timber.

Mixing

No mixing is required, simply use directly from pail.

Precaution

Timber Set is not recommended for installing any timber flooring over concrete, this application should be carried out with Bostik Ultraset (refer technical bulletin).

Do not apply below 10°C or above 35°C.

Ensure the substrate is porous to enable Timber Set to achieve sufficient bond. Do not apply over existing coatings as bond will be effected.

Clean-Up

Clean up uncured material and equipment immediately after use with water or Bostik-Handi clean towels.

Properties

Colour	Brown & Yellow
Appearance	Soft smooth paste
Base material	EVA latex
Solids	82% +/- 1%
Drying time	15-30 min @ 20°C
Coverage	0.80 – 1.0M ² /Litre
Shelf life	12 months unopened container

Coverage

Approximately 0.8 - 1m² / litre depending on substrate conditions

Health and Safety

- On contact, uncured adhesive may cause irritation.
- Gloves and protective goggles must be worn during application and use.
- Avoid contact with skin, eyes and avoid breathing in vapour
- Wear protective gloves when mixing or using
- If poisoning occurs, contact a doctor or Poisons Information Centre
- If swallowed, do not induce vomiting. Give a glass of water
- If skin contact occurs, remove contaminated clothing and wash skin thoroughly for a minimum of 15 minutes and see a doctor.
- For more detailed information refer to Material Safety Data Sheet

Storage

Store between 5°C and 30°C. Shelf life is twelve months in original unopened pail.

Packaging

15 litre pails

Product Details

Item No	Stock Size	Units/Ctn
377996	16kg	Brown

The representations and recommendations regarding the products are based on tests which we believe to be reliable. However, no guarantee of their accuracy can be made because of the great range of field conditions and variations encountered in raw materials, manufacturing equipment and methods. Thus, the products are sold with a limited warranty only, and on the condition that purchasers will make their own tests to determine the suitability of the product for their particular purposes. Under no circumstances will Bostik Findley Australia Pty Ltd be liable to anyone except for replacement of the products or refund of the purchase price.

ALL SALES ARE EXPRESSLY LIMITED TO THE TERMS AND CONDITIONS OF SALE OF BOSTIK FINDLEY AUSTRALIA PTY LTD FOR FURTHER INFORMATION

Head Office Bostik Australia Pty Ltd, 51-71 High Street, Thomastown Vic 3074
A.B.N. 79 003 893 838
Phone: (03) 9279 9333 Fax: (03) 9261 4744
Phone Construction/ASA: Toll free 1300 364 710

Product construction.australia@bostik.com
Enquires:



Quality endorsed ISO9001 (Thomastown site)
TS16949 (Automotive)

Product: Bostik Timberset
Issue Date: September 2014
Issue No. 2
Author: SH
Division: Construction
Total Pages: 2