



# PRODUCT DATA SHEET

## 9MM CUSHION TILE / VINYL STOP


### 9mm Vinyl Stop

RBM Plastic Extrusions 9mm Vinyl Stop is manufactured to act as a finishing strip when running a 2mm vinyl floor up to the edge of a Carpet Tile.

The 9mm Vinyl Stop is manufactured from a Flexible PVC material, that has been formulated to endure high traffic areas with regards to wear. It is also formulated to meet the requirements for the "Best Practise Guidelines for PVC in the Built Environment" Clauses 7.1 & 7.2.

### Product Specifications

	9mm Vinyl Stop
Roll Size	10 mtrs
Width	100.0mm
Height	9.0mm
Material	Flexible PVC
Finish	Matt
Rolls per carton	3 rolls



9mm Vinyl Stop

\* Please note all dimensions are nominal sizes

### Installation Instructions

The floor surface where the 9mm Vinyl Stop is to be laid must be free of any moisture, dirt, dust, oil, cleaning agent or any other foreign matter that might be present around the area.

The adhesive that is recommended to be used with RBM 9mm Vinyl Stop is the MJS Max Bond 102 Super Contact. This can be used for bother Linear Installations and for contoured installations (avoid traffic until cured, approximately 6 hours).

Note: It is recommended that the back side of the 9mm Vinyl Stop be wiped with a rag dipped in white spirits before adhering, and ensure that all residue dries off before adhering.

In all cases please adhere to the manufacturers usage and application recommendations.

### To apply adhesive

1. Apply adhesive to 9mm Vinyl Stop by either brushing or rolling adhesive on. Two Coates are recommended.
2. Ensuring that wall and floor area is clean of foreign matter, brush or roll adhesive onto the area where the 9mm Vinyl Stop is to be applied
3. Allow both area to dry for 10 – 12 minutes, and then press the 9mm Vinyl Stop onto the area it is to be applied to
4. Use hand roller to fit profile into desired area correctly

*NOTE: This information and our technical advice – whether verbal or in writing are given in good faith but without warranty, and this also applies where proprietary rights of third parties are involved. Our advice does not release you from the obligation to check its validity and to test our products as to their suitability for the intended processes and use. Refer to relevant local, state, and federal construction codes and standards for requirements Variations may occur between photographic images, samples and batches in terms of colour, shade, pattern or similar. All measurements are nominal.*



#### QLD

35 Dividend St  
Mansfield  
Ph: 07 3347 7300  
Fax: 07 3343 9792

#### NTH QLD

1 / 12 Civil Road  
Garbutt  
Ph: 07 4728 8644  
Fax: 07 4728 2496

#### NSW

7 Walker Place  
Wetherill Park  
Ph: 02 9725 5519  
Fax: 02 9725 5552

#### ACT

6B / 3 Barrier St  
Fyshwick  
Ph: 02 6239 1000  
Fax: 02 6228 1430

#### VIC

82 Endeavour Way  
Sunshine  
Ph: 03 9314 2872  
Fax: 03 9314 6971

#### TAS

101 Albert Rd  
Moonah  
Ph: 03 6228 1032  
Fax: 03 6228 1035

#### SA

22 Fifth Street  
Bowden  
Ph: 08 8340 2266  
Fax: 08 8340 2188