



## **MB250 – Moisture Block Blue Technical Characteristics**

### **2mm EPE Foam with Double Sided PE film**

- PE foam with closed cell structure
- Thickness supplied: 2mm+double sides 0.04mm PE
- Dimensions: rolls of 50m×1m
- Total surface area: 50 m<sup>2</sup>
- Top side contains reinforced damp-proof membrane in PE
- With self-adhesive strip
- Overlap: 100mm

- ◆ 100% VAPOUR BARRIER
- ◆ 100% ELECTRIC INSULATION
- ◆ 100% MOULD AND MIDEW RESISTANT
- ◆ 100% HEALTH AND ENVIRONMENTAL

- ◆ Density: 25KGS/M3
- ◆ Water vapour trans.rate: ASTM E96 4.8g/m2.24hr
- ◆ Water absorption 28 days: JIS 6767 0.07mg/cm2
- ◆ Compr.strength (25%Comp) ISO844 20kpa
- ◆ Moisture protection SD Value≥75 m



<b><u>QLD</u></b>	<b><u>NTH QLD</u></b>	<b><u>NSW</u></b>	<b><u>ACT</u></b>	<b><u>VIC</u></b>	<b><u>TAS</u></b>	<b><u>SA</u></b>
35 Dividend St	1/ 12 Civil Road	2/ 4-7 Potter Close	6B / 3 Barrier St	82 Endeavour Way	101 Albert Rd	22 Fifth Street
Mansfield	Garbutt	Wetherill Park	Fyshwick	Sunshine	Moonah	Bowden
Ph: 07 3347 7300	Ph: 07 4728 8644	Ph: 02 9725 5519	Ph: 02 6239 1000	Ph: 03 9314 2872	Ph: 03 6228 1032	Ph: 08 8340 2266
Fax: 07 3343 9792	Fax: 07 4728 2496	Fax: 02 9725 5552	Fax: 02 6228 1430	Fax: 03 9314 6971	Fax: 03 6228 1035	Fax: 08 8340 2188