

Product Data Sheet



MAX BOND ENVIRO

2020 HP Sheet Vinyl Adhesive

PRODUCT DESCRIPTION

MAX BOND ENVIRO 2020 is High Performance Floor & Wall Sheet Vinyl Adhesive with extended work time & Low VOC that conforms to the Green Star Building Standard. It is a polymer blend based adhesive designed for the installation of commercial and domestic sheet vinyl. Suitable for Carpet floorcoverings. It is not recommended for the installation of LVP or LVT.

It has an excellent plasticizer resistance and is formulated to provide long open times and exhibit excellent "re-bond" characteristics. Internal use only

SURFACE PREPARATION

To be in accordance with The current Australian/NZ Standard 1884 "Floor Coverings – Resilient Sheet and Tiles – Laying and Maintenance Practices". All surfaces to be bonded shall be dry, smooth, sound and clean. Subfloors must also be free of wax, grease and hydrostatic pressure. The minimum subfloor temperature before commencing surface preparation and adhesive applications should be greater than 10 degrees C. Substrate must be absorbent to enable the adhesive to dry & cure.

Highly absorbent wooden or concrete subfloor surfaces are to be primed with MAX BOND Primer prior to the application of adhesive.

All concrete substrate floors should be tested for moisture content, according to the above Australian/NZ Standard prior to undertaking surface priming or installation of floorcoverings.

APPLICATION

Spread adhesive with a 1.6mm x 1.6mm x 1.6mm 'V' Notched trowel. Some domestic sheet vinyl may require a fine 1.6mm x 0.8 x .08 trowel to prevent adhesive 'show through'. Adhesive can be allowed to tack-up before floorcoverings is lowered. Tack-up time will depend upon

atmospheric conditions and can be anywhere between 10-20 minutes. It is good practice to place a small piece of floorcoverings into the adhesive. When the floorcovering is pulled away, strings of adhesive should be apparent. If no tack or holding power has developed, wait five minutes before rechecking every few minutes thereafter. Always ensure wet transfer has accrued to floorcovering for best result.

Complete installation according to vinyl manufacturer's instructions, ensuring the installation is rolled in both directions with the recommended roll weight, prior to the adhesive setting. Do not allow heavy traffic for 24 hours.

All seams for domestic vinyl should be seam-sealed using suitable vinyl seam sealer.

CLEAN UP

Clean tools immediately after use with warm soapy water. Dried adhesive may be cleaned off using a solvent cleaner applied to a damp cloth then rubbed gently over the dried adhesive.

TYPICAL PROPERTIES

Appearance	Cream / White
Base	Polymer Blend
Solids	Approx 70%
Viscosity	Creamy Paste
Shelf Life	Up to 1 year in sealed container at 20°C
Freezability	Do not freeze
Container Size	15 Litre plastic pail
Tack-up	10-15 minutes at 20°C

Note: Always carry out your own test to confirm suitability of this product with your application.

Additional information on physical properties, health hazards, storage, handling and transport is available in the Material Safety Data Sheet (MSDS), available on MJS web site.



Floorcoverings
November
2017

DISTRIBUTED BY:

QUEENSLAND

Brisbane
MJS Floorcoverings
35 Dividend St
Mansfield 4122
Ph: 07 3347 7300
Fax: 1800 063 299

NSW

Sydney
MJS Floorcoverings
Unit 2, 4-7 Potter
Close
Wetherill Park 2164
Ph: 02 9725 5519
Fax: 02 9725 5552

VICTORIA

Melbourne
MJS Floorcoverings
82 Endeavour St
Sunshine 3020
Ph: 03 9314 2872
Fax: 03 9314 6971

TASMANIA

Hobart
MJS Floorcoverings
101 Albert Rd
Moonah 7000
Ph: 03 6228 1032
Fax: 03 6228 1035

NORTHERN TERRITORY

Darwin
MJS Floorcoverings
4, 124 Coonawarra Rd
Winnellie 0821
Ph: 08 8947 6917
Fax: 08 8947 1528

SOUTH AUSTRALIA

Adelaide
MJS Floorcoverings
22 Firth St
Bowden 5007
Ph: 08 8340 2266
Fax: 08 8340 2188

WESTERN AUSTRALIA

Perth
MANAG Distributors
28 Carbon Court
Osborne Park 6017
Ph: 08 6240 1000
Fax: 08 9445 1332