

Product Data Sheet



Max Bond



101 SKIRTING CONTACT ADHESIVE

PRODUCT DESCRIPTION

Max Bond 101 Skirting Contact Adhesive is a specifically formulated high solids, high heat resistant, non-stringing solvent based adhesive. It is a fast drying, brushable or rollable, contact adhesive, displaying high early bond strength. Max Bond 101 Skirting Contract Adhesive is designed for use on most types of vinyl skirting and PVC mouldings. Suitable for all types of subfloors including concrete, wood, metal, ceramic, terrazzo and concrete. Ideal for bonding most types of conventional interior carpet to stair treads and risers. *Not recommended for exterior application.*

SURFACE PREPARATION

Ensure the surface is even, clean, dry and free from oil, dust or other contaminants.

APPLICATION

Mix thoroughly before use. Adhesive must be brushed or rolled onto both surfaces using appropriate brush or roller. Allow solvent to evaporate and adhesive to become touch dry. This will take approx. 10-15 minutes depending on substrate porosity, texture, ambient temperature and airflow. Ideally the surfaces should be brought together within 45 minutes. On porous surfaces a second application of adhesive may be required. Pressure should be applied to the entire area once surfaces are brought together. Do not apply adhesive if temperature is below 10°C.

Refer to AS/NZS2455.1-2007 "Textile Floor Coverings – Installation Practice" and current AS1884 for further preparation and installation details.

CLEAN UP

While adhesive is still wet or tacky, clean up with MAX BOND SC Solvent Cleaner. **Note:** MAX BOND SC is not recommended for removing adhesive from vinyl & carpet or finished surfaces.

STORAGE

Store in moderately cool and dry conditions, preferably suspended off the concrete substrate. In cold climates, product should be stored at approx. 21°C on pallets or racks, providing clearance from concrete floors.

TYPICAL PROPERTIES

Appearance:	Liquid Base: Polychloroprene rubber
Viscosity:	Thin Syrup
Tack Up:	Approx 10 – 15 minutes at 20°C
Open Time:	Approx 45 minutes
Shelf Life:	12 months from date of manufacture when stored in a cool, dry, environment
Flammable Liquid:	3

PACKAGING: 4 litre cans and 20 litre metal pails
Coverage Approx 3 - 4m² per litre

Note: Always carry out your own test to confirm suitability of this product with your application. Additional information on physical properties, health hazards, storage, handling and transport is available in the Material Safety Data Sheet (MSDS), available on MJS web site.

February 2019



QUEENSLAND Brisbane	NSW Sydney	VICTORIA Melbourne	TASMANIA Hobart	NORTHERN TERRITORY Darwin	SOUTH AUSTRALIA Adelaide	WESTERN AUSTRALIA Perth
MJS Floorcoverings 35 Dividend St Mansfield 4122 Ph: 07 3347 7300 Fax: 07 3343 9792	MJS Floorcoverings 2/4-7 Potter Close Wetherill Park 2164 Ph: 02 9616 1500 Fax: 02 9616 1502	MJS Floorcoverings 82 Endeavour St Sunshine 3020 Ph: 03 9351 7400 Fax: 03 9351 7402	MJS Floorcoverings 101 Albert Rd Moonah 7000 Ph: 03 6242 8800 Fax: 03 6242 8802	MJS Floorcoverings Unit 4/124 Coonawarra Rd Winnellie NT 0821 Ph: 08 7922 9700 Fax: 08 7922 9702	MJS Floorcoverings 22 Ridley Street Hindmarsh SA 5007 Ph: 08 8178 5300 Fax: 08 8178 5302	MJS Floorcoverings Opening 2019