

Product Data Sheet



MAX BOND ENVIRO



2001 TRU SET TIMBER ADHESIVE

PRODUCT DESCRIPTION

Maxbond Enviro 2001 Tru Set Timber adhesive is a one-part moisture cure Polyurethane Adhesive. It is solvent free and low in VOC content. When fully cured it forms a water resistant flexible film. 2001 Tru Set is 100% solids and has excellent sound absorbing qualities.

For Bonding: Specially formulated for the installation of both block, mosaic parquetry, engineered wood floors, laminated timber & Sheet timber flooring.

This adhesive is suitable for use over absorbent heated subfloors. Please refer to AS1884-2012 including clause 4.1.3 that explains time heating needs to be turned off for.

TO

Sound, smooth dry subfloors of concrete, plywood or cement sheet underlays and most common building substrates. 2001 Tru Set Polyurethane Adhesive can be adhered directly to most common epoxy "Moisture Barriers".

SURFACE PREPARATION

All surfaces to be bonded should be dry, smooth, and free of any contaminants that may affect final bond. All surfaces must be prepared in accordance with current Australian/NZ Standards 1884 Floor Coverings Resilient Sheet including moisture testing. The minimum sub floor temperature prior to commencing preparation or adhesive application is 10°C.

It is strongly recommended that Enviro 2000 Tru Seal Moisture Barrier be used over concrete floors prior to installing Timber Floorcoverings.

DIRECTION FOR USE

Apply adhesive using a 3 - 4mm "V" notched spreader. Coverage should be in the vicinity of 1.5m² per litre. Floorcovering should be laid into wet adhesive. Complete installation according to manufactures instructions. Do not allow heavy traffic for 24 hours.

CLEAN UP

Clean tools immediately using Max Bond Solvent Cleaner. Mechanical means are necessary when dry.

TYPICAL PROPERTIES

Appearance	Beige / Brown
Base	Polyurethane
Solids	Approx 100%
Viscosity	Trowellable
Shelf Life	Up to 1 year from manufacturing date in sealed container at 20°C
Freezability	Do not freeze
Packaging	10 Litre Metal pail & 600ml Sausages

Note: Always carry out your own test to confirm suitability of this product with your application. Additional information on physical properties, health hazards, storage, handling and transport is available in the Material Safety Data Sheet (MSDS), available on MJS web site

February 2019



Floorcoverings



Floorcoverings

QUEENSLAND
Brisbane
MJS Floorcoverings
35 Dividend St
Mansfield 4122
Ph: 07 3347 7300
Fax: 07 3343 9792

NSW
Sydney
MJS Floorcoverings
2/4-7 Potter Close
Wetherill Park 2164
Ph: 02 9616 1500
Fax: 02 9616 1502

VICTORIA
Melbourne
MJS Floorcoverings
82 Endeavour St
Sunshine 3020
Ph: 03 9351 7400
Fax: 03 9351 7402

TASMANIA
Hobart
MJS Floorcoverings
101 Albert Rd
Moonah 7000
Ph: 03 6242 8800
Fax: 03 6242 8802

NORTHERN TERRITORY
Darwin
MJS Floorcoverings
Unit 4/124 Coonawarra Rd
Winnellie NT 0821
Ph: 08 7922 9700
Fax: 08 7922 9702

SOUTH AUSTRALIA
Adelaide
MJS Floorcoverings
22 Ridley Street
Hindmarsh SA 5007
Ph: 08 8178 5300
Fax: 08 8178 5302

WESTERN AUSTRALIA
Perth
MJS Floorcoverings
Opening 2019