

Product Data Sheet



MAX BOND ENVIRO



2004 CARPET TILE & DOUBLE BOND CUSHION ADHESIVE

PRODUCT DESCRIPTION

MAX BOND ENVIRO 2004 Pressure Sensitive adhesive is Low VOC that conforms to the Green Star Building Standards and has been developed for the installation of Carpet Tiles and Double Bond underlay's used in the double bond carpet installation. It has good plasticiser resistance. Internal use only

SURFACE PREPARATION

To be in accordance with The current Australian/NZ Standard 1884 & 2455 All surfaces to be bonded shall be dry, smooth, sound and clean. Subfloors must also be free of wax, grease and hydrostatic pressure. The minimum subfloor temperature before commencing surface preparation and adhesive applications 10 degrees C.

Highly absorbent wooden or concrete subfloor surfaces are to be primed with MAX BOND Primer prior to the application of adhesive.

All concrete substrate floors should be tested for moisture content, according to the above Australian/NZ Standard prior to undertaking surface priming or installation of floorcoverings.

This adhesive is suitable for use over absorbent heated subfloors. Please refer to AS1884-2012 including clause 4.1.3 that explains time heating needs to be turned off for.

DIRECTION FOR USE

For textured backed double bond underlays, apply adhesive using a 1.6mm x 1.6mm x 1.6mm "V" notched spreader with approx coverage of 5m² per litre.

When installing Carpet Tiles and smooth backed Double Bond underlay, use a long nap roller with approx coverage of 7m² per litre.

MAX BOND ENVIRO 2004 has been designed to be used in dry mode i.e. allow the adhesive film to completely dry and become clear.

Clear is when the adhesive changes from white wet adhesive to dry clear tacky film of adhesive. Clear time will depend on atmospheric conditions.

Complete installation according to manufacturers instruction. Roll installation on completion with the recommended weight roller.

Do not allow heavy traffic for 24 hours

When installing Carpet Tiles onto double bond underlay use Max Bond 2009

CLEAN UP

Clean tools immediately after use with warm soapy water. Dried adhesive may be softened using a suitable solvent.

TYPICAL PROPERTIES

Base	Acrylic
Solids	Approx 44%
Shelf Life	12 months from manufacturing date in sealed container at 20°C
Packaging	15 Litre pails

Note: Always carry out your own test to confirm suitability of this product with your application. Additional information on physical properties, health hazards, storage, handling and transport is available in the Material Safety Data Sheet (MSDS), available on MJS web site.

February 2019



QUEENSLAND
Brisbane
MJS Floorcoverings
35 Dividend St
Mansfield 4122
Ph: 07 3347 7300
Fax: 07 3343 9792

NSW
Sydney
MJS Floorcoverings
2/4-7 Potter Close
Wetherill Park 2164
Ph: 02 9616 1500
Fax: 02 9616 1502

VICTORIA
Melbourne
MJS Floorcoverings
82 Endeavour St
Sunshine 3020
Ph: 03 9351 7400
Fax: 03 9351 7402

TASMANIA
Hobart
MJS Floorcoverings
101 Albert Rd
Moonah 7000
Ph: 03 6242 8800
Fax: 03 6242 8802

NORTHERN TERRITORY
Darwin
MJS Floorcoverings
Unit 4/124 Coonawarra Rd
Winnellie NT 0821
Ph: 08 7922 9700
Fax: 08 7922 9702

SOUTH AUSTRALIA
Adelaide
MJS Floorcoverings
22 Ridley Street
Hindmarsh SA 5007
Ph: 08 8178 5300
Fax: 08 8178 5302

WESTERN AUSTRALIA
Perth
MJS Floorcoverings
Opening 2019