

# Product Data Sheet



## MAX BOND ENVIRO



### 2009 "SUPER" P.S ADHESIVE

#### PRODUCT DESCRIPTION

MAX BOND ENVIRO 2009 Pressure Sensitive adhesive is Low VOC that conforms to the Green Star Building Standards and has been developed for the installation of vinyl composition tiles. It is also suitable for the installation of Carpet Tiles and slab underlay's used in the double bond carpet installation. It has good plasticiser resistance. Internal use only

This adhesive is suitable for use over absorbent heated subfloors. Please refer to AS1884-2012 including clause 4.1.3 that explains time heating needs to be turned off for.

#### SURFACE PREPARATION

To be in accordance with The current Australian/NZ Standard 1884 & 2455 All surfaces to be bonded shall be dry, smooth, sound and clean. Subfloors must also be free of wax, grease and hydrostatic pressure. The minimum subfloor temperature before commencing surface preparation and adhesive applications 10 degrees C.

Highly absorbent wooden or concrete subfloor surfaces are to be primed with MAX BOND Primer prior to the application of adhesive.

All concrete substrate floors should be tested for moisture content, according to the above Australian/NZ Standard prior to undertaking surface priming or installation of floorcoverings.

#### DIRECTION FOR USE

For the installation of composition tiles, textured backed double bond underlays & Carpet Tiles to double bond underlay apply adhesive using a 1.6mm x 1.6mm x 1.6mm "V" notched spreader with approx coverage of 5m<sup>2</sup> per litre for.

When installing Carpet Tiles and smooth backed Double Bond underlay, use a long nap roller with approx coverage of 7m<sup>2</sup> per litre.

MAX BOND ENVIRO 2009 has been designed to be used in dry mode ie allow the adhesive film to completely dry and become clear.

Clear is when the adhesive changes from white wet adhesive to dry clear tacky film of adhesive. Clear time will depend on atmospheric conditions.

Complete installation according to manufacture instructions. Roll installation on completion with the recommended weight roller.

Do not allow heavy traffic for 24 hours

#### CLEAN UP

Clean tools immediately after use with warm soapy water. Dried adhesive may be softened using a suitable solvent.

#### TYPICAL PROPERTIES

Base: Acrylic  
Solids: Approx 50%  
Shelf Life: 12 months from manufacturing date in sealed container at 20°C  
Packaging: 4 & 15 Litre pails

*Note: Always carry out your own test to confirm suitability of this product with your application. Additional information on physical properties, health hazards, storage, handling and transport is available in the Material Safety Data Sheet (MSDS), available on MJS web site.*

February 2019



Floorcoverings



Floorcoverings

**QUEENSLAND**  
**Brisbane**  
MJS Floorcoverings  
35 Dividend St  
Mansfield 4122  
Ph: 07 3347 7300  
Fax: 07 3343 9792

**NSW**  
**Sydney**  
MJS Floorcoverings  
2/4-7 Potter Close  
Wetherill Park 2164  
Ph: 02 9616 1500  
Fax: 02 9616 1502

**VICTORIA**  
**Melbourne**  
MJS Floorcoverings  
82 Endeavour St  
Sunshine 3020  
Ph: 03 9351 7400  
Fax: 03 9351 7402

**TASMANIA**  
**Hobart**  
MJS Floorcoverings  
101 Albert Rd  
Moonah 7000  
Ph: 03 6242 8800  
Fax: 03 6242 8802

**NORTHERN TERRITORY**  
**Darwin**  
MJS Floorcoverings  
Unit 4/124 Coonawarra Rd  
Winnellie NT 0821  
Ph: 08 7922 9700  
Fax: 08 7922 9702

**SOUTH AUSTRALIA**  
**Adelaide**  
MJS Floorcoverings  
22 Ridley Street  
Hindmarsh SA 5007  
Ph: 08 8178 5300  
Fax: 08 8178 5302

**WESTERN AUSTRALIA**  
**Perth**  
MJS Floorcoverings  
Opening 2019