

Product Data Sheet



MAX BOND ENVIRO

2011 LINOLEUM ADHESIVE



PRODUCT DESCRIPTION

MAX Bond ENVIRO 2011 is a water-based Latex adhesive. It has been specifically formulated to provide aggressive "leggy" grab and holding power once the adhesive has tacked up.

FOR BONDING

Linoleum sheet and tile products.

TO

Sound, smooth dry subfloors of concrete; conventional sand/cement screeds or underlayment; plywood; hardboard or cement sheet underlays.

This adhesive is suitable for use over absorbent heated subfloors. Please refer to AS1884-2012 including clause 4.1.3 that explains time heating needs to be turned off for.

STANDARDS

Current Australian/NZ Standard 1884 – Resilient Sheet & Tiles – Laying & Maintenance Practices or current relevant standards.

SURFACE PREPARATION

All surfaces to be bonded shall be dry, smooth, sound and clean. Subfloors must also be free of wax, grease and hydrostatic pressure. The minimum subfloor temperature before commencing surface preparation and adhesive application is 10°C. It is recommended that all absorbent substrates be primed with MAX BOND Primer prior to the application of adhesive. Substrate must be absorbent to enable the adhesive to dry & cure.

TECHNICAL DATA

Appearance:	Cream / Beige
Solids:	Approx 75%
Base Polymer:	Latex
Viscosity:	Creamy Paste
Toxicity:	Non-toxic
S.G.:	Approx 1.25
Freezability:	Avoid freezing

APPLICATION

Spread adhesive using a "V2" 2.4mm x 2.4mm x 2.4mm 'V' notched trowel giving a spread rate up to 3m²/litre. Allow adhesive to tack-up before lowering floorcovering into wet film of adhesive.

Check to ensure that complete transfer of adhesive to the Linoleum has occurred. Roll finished installation with a suitable roller. Complete the installation according to the floorcovering manufacturer's instruction. Do not allow heavy traffic for 24 hours.

CLEAN UP

Clean tools immediately after use with warm soapy water. Dried adhesive may be cleaned off using a solvent cleaner applied to a damp cloth then rubbed gently over the dried adhesive.

SHELF LIFE

Up to 12 months from manufacturing date in sealed container at 20°C.

Note: Always carry out your own test to confirm suitability of this product with your application. Additional information on physical properties, health hazards, storage, handling and transport is available in the Material Safety Data Sheet (MSDS), available on MJS web site.

STORAGE

Recommended to be at temperatures between 10 and 30 degrees Celsius. Keep in well-ventilated area away from sources of heat.

CONTAINER SIZES

15 litre plastic pails

February 2019



QUEENSLAND Brisbane

MJS Floorcoverings
35 Dividend St
Mansfield 4122
Ph: 07 3347 7300
Fax: 07 3343 9792

NSW Sydney

MJS Floorcoverings
2/4-7 Potter Close
Wetherill Park 2164
Ph: 02 9616 1500
Fax: 02 9616 1502

VICTORIA Melbourne

MJS Floorcoverings
82 Endeavour St
Sunshine 3020
Ph: 03 9351 7400
Fax: 03 9351 7402

TASMANIA Hobart

MJS Floorcoverings
101 Albert Rd
Moonah 7000
Ph: 03 6242 8800
Fax: 03 6242 8802

NORTHERN TERRITORY Darwin

MJS Floorcoverings
Unit 4/124 Coonawarra Rd
Winnellie NT 0821
Ph: 08 7922 9700
Fax: 08 7922 9702

SOUTH AUSTRALIA Adelaide

MJS Floorcoverings
22 Ridley Street
Hindmarsh SA 5007
Ph: 08 8178 5300
Fax: 08 8178 5302

WESTERN AUSTRALIA Perth

MJS Floorcoverings
Opening 2019

