

Product Data Sheet



Max Bond



M60 CARPET LATEX

DESCRIPTION

MAX BOND M60 Carpet Latex is a Natural Latex compound for sealing raw edges of carpet and installing felt underlay to substrates.

DIRECTION FOR USE

Prior to joining carpet seams with heat bond tape or seam sealer, apply MAX BOND M60 to edge of carpet and allow to dry.

Doing this helps prevent with loss of tufts and unraveling after seams have been trimmed.

When used to install felt underlay to subfloors apply a liberal amount to the subfloor and install underlay into wet latex.

CLEAN UP

Clean tools immediately after use with warm soapy water.

TYPICAL PROPERTIES.

Base:	Natural Latex
Appearance:	White Liquid
Viscosity:	Thin Liquid
Shelf Life:	12 months in sealed container at 20°C
Packaging:	1, 4 & 15 Litre
Odour:	Ammonia
Freezability:	Avoid Freezing

Note: Always carry out your own test to confirm suitability of this product with your application. Additional information on physical properties, health hazards, storage, handling and transport is available in the Material Safety Data Sheet (MSDS), available on MJS web site

February 2019



Floorcoverings

QUEENSLAND Brisbane

MJS Floorcoverings
35 Dividend St
Mansfield 4122
Ph: 07 3347 7300
Fax: 07 3343 9792

NSW Sydney

MJS Floorcoverings
2/4-7 Potter Close
Wetherill Park 2164
Ph: 02 9616 1500
Fax: 02 9616 1502

VICTORIA Melbourne

MJS Floorcoverings
82 Endeavour St
Sunshine 3020
Ph: 03 9351 7400
Fax: 03 9351 7402

TASMANIA Hobart

MJS Floorcoverings
101 Albert Rd
Moonah 7000
Ph: 03 6242 8800
Fax: 03 6242 8802

NORTHERN TERRITORY Darwin

MJS Floorcoverings
Unit 4/124 Coonawarra Rd
Winnellie NT 0821
Ph: 08 7922 9700
Fax: 08 7922 9702

SOUTH AUSTRALIA Adelaide

MJS Floorcoverings
22 Ridley Street
Hindmarsh SA 5007
Ph: 08 8178 5300
Fax: 08 8178 5302

WESTERN AUSTRALIA

MJS Floorcoverings
Opening 2019