

Product Data Sheet



MAX BOND ENVIRO



TTA TEXTILE ADHESIVE

PRODUCT DESCRIPTION

MAX BOND ENVIRO TTA Textile Adhesive is Low VOC that conforms to the Green Star Building Standard. It is a high performance adhesive designed for the installation of Textile / Felt backed Vinyl only over absorbent substrates.

It is not suitable or recommended for the installation of PVC Backed floorcovering Products.

SURFACE PREPARATION

To be in accordance with The current Australian/NZ Standard 1884 "Floor Coverings – Resilient Sheet and Tiles – Laying and Maintenance Practices". All surfaces to be bonded shall be dry, smooth, sound and clean. Subfloors must also be free of wax, grease and hydrostatic pressure. The minimum subfloor temperature before commencing surface preparation and adhesive applications is 10 degrees C. Substrate must be absorbent to enable the adhesive to dry & cure.

Absorbent wooden or concrete subfloor surfaces are to be primed with MAX BOND Primer prior to the application of adhesive.

All concrete substrate floors should be tested for moisture content, according to the above Australian/NZ Standard prior to undertaking surface priming or installation of floorcoverings.

APPLICATION

Spread adhesive with a 1.6mm x 1.6mm x 1.6mm 'V' Notched trowel. Install floorcoverings into wet

adhesive and ensuring complete wet transfer of adhesive to back of floorcovering.

Complete installation according to vinyl manufacturer's instructions, ensuring the installation is rolled in both directions with the recommended roll weight, prior to the adhesive curing. Do not allow heavy traffic for 24 hours.

All seams for domestic vinyl should be seam-sealed using suitable vinyl seam sealer.

CLEAN UP

Clean tools immediately after use with warm soapy water. Dried adhesive on tools may be cleaned off using a solvent cleaner applied to a damp cloth then rubbed gently over the dried adhesive.

TYPICAL PROPERTIES

Appearance	Cream / White
Base	Latex
Solids	Approx 62%
Viscosity	Creamy Paste
Shelf Life	Up to 1 year in sealed container at 20°C
Freezability	Do not freeze
Container Size	15 Litre plastic pail
COVERAGE	Up to 5m ² per litre using "V1" Trowel

Note: Always carry out your own test to confirm suitability of this product with your application. Additional information on physical properties, health hazards, storage, handling and transport is available in the Material Safety Data Sheet (MSDS), available on MJS web site.

February 2019



QUEENSLAND
Brisbane
MJS Floorcoverings
35 Dividend St
Mansfield 4122
Ph: 07 3347 7300
Fax: 07 3343 9792

NSW
Sydney
MJS Floorcoverings
2/4-7 Potter Close
Wetherill Park 2164
Ph: 02 9616 1500
Fax: 02 9616 1502

VICTORIA
Melbourne
MJS Floorcoverings
82 Endeavour St
Sunshine 3020
Ph: 03 9351 7400
Fax: 03 9351 7402

TASMANIA
Hobart
MJS Floorcoverings
101 Albert Rd
Moonah 7000
Ph: 03 6242 8800
Fax: 03 6242 8802

NORTHERN TERRITORY
Darwin
MJS Floorcoverings
Unit 4/124 Coonawarra Rd
Winnellie NT 0821
Ph: 08 7922 9700
Fax: 08 7922 9702

SOUTH AUSTRALIA
Adelaide
MJS Floorcoverings
22 Ridley Street
Hindmarsh SA 5007
Ph: 08 8178 5300
Fax: 08 8178 5302

WESTERN AUSTRALIA
Perth
MJS Floorcoverings
Opening 2019