

Product Data Sheet



Max Bond



VSS VINYL SEAM SEALER

DESCRIPTION

MAX BOND VSS Vinyl Seam Sealer is a solvent based adhesive designed for the chemically welding of domestic vinyl sheet flooring seams.

DIRECTIONS FOR USE

All seams must be clean and dry prior to seam sealing.
Transfer MAX BOND VSS Vinyl Seam Sealer to applicator bottle.
Starting at one end of seam insert applicator tip into seam and apply a continuous bead along the entire length of the seam.
Avoid excess seam sealer on surface of floor covering.

CLEAN UP

Clean tools immediately after use with MAX BOND Solvent Cleaner.
MAX BOND Solvent Cleaner is not suitable for use on Vinyl, Carpets or any finished surface.

TYPICAL PROPERTIES

- Appearance: Clear Liquid
- Viscosity: Thin Liquid
- Shelf Life: 12 months in sealed container at 20°C
- Packaging: 500ml Cans

Note: Always carry out your own test to confirm suitability of this product with your application. Additional information on physical properties, health hazards, storage, handling and transport is available in the Material Safety Data Sheet (MSDS), available on request.



Floorcoverings

QUEENSLAND Brisbane

MJS Floorcoverings
35 Dividend St
Mansfield 4122
Ph: 07 3347 7300
Fax: 07 3343 9792

NSW Sydney

MJS Floorcoverings
2/4-7 Potter Close
Wetherill Park 2164
Ph: 02 9616 1500
Fax: 02 9616 1502

VICTORIA Melbourne

MJS Floorcoverings
82 Endeavour St
Sunshine 3020
Ph: 03 9351 7400
Fax: 03 9351 7402

TASMANIA Hobart

MJS Floorcoverings
101 Albert Rd
Moonah 7000
Ph: 03 6242 8800
Fax: 03 6242 8802

NORTHERN TERRITORY Darwin

MJS Floorcoverings
Unit 4/124 Coonawarra Rd
Winnellie NT 0821
Ph: 08 7922 9700
Fax: 08 7922 9702

SOUTH AUSTRALIA Adelaide

MJS Floorcoverings
22 Ridley Street
Hindmarsh SA 5007
Ph: 08 8178 5300
Fax: 08 8178 5302

WESTERN AUSTRALIA Perth MJS Floorcoverings Opening 2019